

Product	Specification
<p style="text-align: center;">DELL EMC PowerEdge FC630 Server Node</p>	<ul style="list-style-type: none"> • 2x Intel Xeon E5-2650 v4 2.2GHz,30M Cache,9.60GT/s QPI,Turbo,HT,12C/24T (105W) Max Mem 2400MHz • PowerEdgeFC PCIE Mezzanine Adapter, Slot Reassignment Mode for Remapping of Available FX2S PCI Slots <ul style="list-style-type: none"> • Performance Optimized • 4x 32GB RDIMM, 2400MT/s, Dual Rank, x4 Data Width <ul style="list-style-type: none"> • DIMM Blanks for System with 2 Processors • iDRAC8 Enterprise, integrated Dell Remote Access Controller, Enterprise • 2x 120GB Solid State Drive SATA Boot MLC 6Gpbs 2.5in Hot-plug Drive,13G <ul style="list-style-type: none"> • H330 Controller • 2.5" Backplane with up to 2 Hard Drives and PERC RAID Controller • Emulex LPe16002B, Dual Port 16Gb Fibre Channel HBA, Low Profile <ul style="list-style-type: none"> • Standard Cooling,FC630 • 2x 68MM Heatsink for PowerEdge FC630 • PowerEdge FC PCIE Mezzanine Adapter • QLogic 57810-k Dual port 10Gb KR CNA Blade Network Daughter Card

Product	Specification
<p style="text-align: center;">DELL EMC FX2 Chassis</p>	<ul style="list-style-type: none"> • PowerEdge FX2 Chassis for up to 4 Half-Width Nodes • PowerEdge FX2S Chassis Configuration with Flexible IO (up to 8 PCIe Slots) <ul style="list-style-type: none"> • 2x FX2 Half-Width Node Filler Blank • SD Storage for Chassis Management Controller • Serial I/O Management Cable, for Ethernet Blade Switches • Dual,Hot-plug Power Supply , 2400W,250 Volt Power Cord Required for Use <ul style="list-style-type: none"> • 2x Jumper Cord, 230V,2.5M,C19/C20 <ul style="list-style-type: none"> • CMC Enterprise for FX2 • Redundant Ethernet Switch Configuration <ul style="list-style-type: none"> • FX2 ReadyRails Sliding Rails